



HI TECH METALLICS AND LACQUERS

A fast drying lacquer based spray paint that provides durable indoor and outdoor protection. Resistant to the effects of weather and many chemicals. Resists abrasion and heat (250F). Bare surfaces or rusted metal surfaces should first be primed with our Hi-Tech primers to ensure proper adhesion.

Suggested Uses:

Home
Automotive
Industrial
Marine
Construction

Packaging:

Cans per case	6
Shipping weight per case	7 lbs.
Container	16 fluid ounce can
Label weight	12 ounces (340 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 15 square feet
Cleanup	Paint or lacquer thinner
Flash point	-4F
Specific Gravity	0.86
Solids Content	Glosses: ~15%
	Flats: ~15%
	Metallics: ~13%
MIR value	Glosses: 0.86, cannot exceed 0.95
	Clear: 0.82, cannot exceed 0.85
	Metallics: 1.17, cannot exceed 1.25
HAPs content	Glosses: ~13%
	Clear: ~25%
	Metallics: ~30%
Storage Temperature	40-100F
Application Temperature	50-90F
Durability	Good
Abrasion Resistance	Good
Gasoline Resistance	No
Heat Resistance	250F
Resin System	Acrylic lacquer
Shelf life	Guaranteed for 2 years

Dry Time*:

Tack free	5 minutes
To recoat	20 minutes

*At 72F, 50% humidity,
1.5 mil thickness

**Curing/Recoat time is extended with
multiple coats and excessively thick coats**

Gloss*:	High Gloss, >80
	Semi-Gloss, 10-20
	Flat, <15

*as measured on a 60 degree gloss meter

Available Colors:

Part #	Description	UPC Code	Part #	Description	UPC Code
16-111	Shiny Aluminum	043281000123	16-815	Gloss Black Lacquer	043281001021
16-121	Gloss Clear Acrylic	043281000215	16-821	Gloss Clear Lacquer	043281001038
16-132	Dull Aluminum Metallic	043281000291	16-838	Semi-Gloss Black	043281001069
16-806	Dull Black	043281000987	EN-41	Aluminum	043281003728
16-812	Gold Metallic	043281001007	EN-50	Gold	043281003797
16-813	Gloss White Lacquer	043281001014			

12-19-2019