

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.06.2018

Page 1 of 13

## Self-Etch Primer - Aerosol

### SECTION 1: Identification

#### Product identifier

**Product name:** Self-Etch Primer - Aerosol

**Product code:** 41018



#### Recommended use of the product and restriction on use

**Relevant identified uses:** Paints and coatings.

**Uses advised against:** Not determined or not applicable.

**Reasons why uses advised against:** Not determined or not applicable.

#### Manufacturer or supplier details

##### Manufacturer:

##### United States

P.O.R. Products

38 Portman Road

New Rochelle, NY 10801

914-636-0700

#### Emergency telephone number:

##### United States

##### ChemTel Inc.

+1 800 255 3924

+1 813 248 0585

### SECTION 2: Hazard(s) identification

#### GHS classification:

Flammable aerosols, category 1

Compressed gases


Eye irritation, category 2A

Specific target organ toxicity - single exposure, category 3, central nervous system

Specific target organ toxicity - repeated exposure, category 2

#### Label elements

##### Hazard pictograms:



**Signal word:** Danger

#### Hazard statements:

H222 Extremely flammable aerosol

H280 Contains gas under pressure; may explode if heated

H319 Causes serious eye irritation

H336 May cause drowsiness or dizziness

H373 May cause damage to organs through prolonged or repeated exposure

#### Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking

P211 Do not spray on an open flame or other ignition source

P251 Pressurized container. Do not pierce or burn, even after use

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.06.2018

Page 2 of 13

## Self-Etch Primer - Aerosol

P264 Wash skin thoroughly after handling  
P280 Wear protective gloves/protective clothing/eye protection/face protection  
P271 Use only outdoors or in a well-ventilated area  
P260 Do not breathe dust/fume/gas/mist/vapors/spray  
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing  
P304+P340+P312 If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell  
P314 Get medical advice/attention if you feel unwell  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F  
P410+P403 Protect from sunlight. Store in a well ventilated place  
P405 Store locked up  
P403+P233 Store in a well ventilated place. Keep container tightly closed  
P501 Dispose of contents and container as instructed in Section 13

**Hazards not otherwise classified:** None

## SECTION 3: Composition/information on ingredients

| Identification            | Name                | Weight % |
|---------------------------|---------------------|----------|
| CAS number:<br>67-63-0    | Isopropyl Alcohol   | 7-12     |
| CAS number:<br>64742-47-8 | Mineral Spirits     | <2       |
| CAS number:<br>108-65-6   | PM Acetate          | <2       |
| CAS number:<br>13463-67-7 | Titanium Dioxide    | 3-8      |
| CAS number:<br>67-64-1    | Acetone             | 20-25    |
| CAS number:<br>78-93-3    | Methyl ethyl ketone | 15-20    |
| CAS number:<br>74-98-6    | Propane             | 12-17    |
| CAS number:<br>106-97-8   | n-Butane            | 7-12     |
| CAS number:<br>557-05-1   | Zinc stearate       | <3       |
| CAS number:<br>2807-30-9  | Glycol Ether EP     | <3       |

**Additional Information:** None

## SECTION 4: First aid measures

### Description of first aid measures

#### General notes:

Not determined or not applicable.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.06.2018

Page 3 of 13

## Self-Etch Primer - Aerosol

### After inhalation:

Loosen clothing as necessary and position individual in a comfortable position  
Maintain an unobstructed airway  
Get medical advice/attention if you feel unwell

### After skin contact:

Rinse affected area with soap and water  
If symptoms develop or persist, seek medical attention

### After eye contact:

Rinse/flush exposed eye(s) gently using water for 15-20 minutes  
If symptoms develop or persist, seek medical attention  
Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open  
Remove contact lenses, if present and easy to do so  
Continue rinsing for 15-20 minutes  
Get medical advice if eye irritation persists

### After swallowing:

Rinse mouth thoroughly  
Seek medical attention if irritation, discomfort, or vomiting persists

### Most important symptoms and effects, both acute and delayed

#### Acute symptoms and effects:

Not determined or not applicable.

#### Delayed symptoms and effects:

Not determined or not applicable.

### Immediate medical attention and special treatment

#### Specific treatment:

Not determined or not applicable.

#### Notes for the doctor:

Not determined or not applicable.

## SECTION 5: Firefighting measures

### Extinguishing media

#### Suitable extinguishing media:

Use Water (fog only), dry chemical, chemical foam, carbon dioxide, or alcohol-resistant foam

#### Unsuitable extinguishing media:

Not determined or not applicable.

### Specific hazards during fire-fighting:

Thermal decomposition can lead to release of irritating gases and vapors  
Contents under pressure  
In a fire or if heated, a pressure increase will occur and the container may burst or explode  
Vapors can flow to distant ignition sources and flashback  
Liquid is volatile and may generate an explosive atmosphere

### Special protective equipment for firefighters:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit

### Special precautions:

Shut off sources of ignition  
Carbon monoxide and carbon dioxide may form upon combustion  
Heating causes a rise in pressure, risk of bursting and combustion

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.06.2018

Page 4 of 13

## Self-Etch Primer - Aerosol

### SECTION 6: Accidental release measures

#### Personal precautions, protective equipment and emergency procedures:

- Ensure adequate ventilation
- Ensure air handling systems are operational
- Wear protective eye wear, gloves and clothing
- Beware of vapors accumulating to form explosive concentrations
- Vapors can accumulate in low areas

#### Environmental precautions:

- Should not be released into the environment
- Prevent from reaching drains, sewer or waterway

#### Methods and material for containment and cleaning up:

- Wear protective eye wear, gloves and clothing
- Use spark-proof tools and equipment
- Absorb with non-combustible liquid-binding material (sand, diatomaceous earth (clay), acid binders, universal binders)
- Dispose of contents / container in accordance with local regulations

#### Reference to other sections:

- Not determined or not applicable.

### SECTION 7: Handling and storage

#### Precautions for safe handling:

- Use only with adequate ventilation.
- Avoid breathing mist or vapor.
- Do not eat, drink, smoke or use personal products when handling chemical substances.
- Do not puncture, crush, or incinerate containers, even when empty.
- Protect cylinders from physical damage.

#### Conditions for safe storage, including any incompatibilities:

- Protect from freezing and physical damage.
- Protect from direct sunlight.
- Store in a cool, well-ventilated area.
- Store cylinders upright.
- Store away from all ignition sources (open flames, hot surfaces, direct sunlight, spark sources).

### SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

#### Occupational Exposure limit values:

| Country (Legal Basis) | Substance           | Identifier | Permissible concentration                |
|-----------------------|---------------------|------------|--|
| ACGIH                 | n-Butane            | 106-97-8   | ACGIH STEL 1,000 ppm                     |
|                       | Propane             | 74-98-6    | ACGIH TLV TWA 2,500 ppm                  |
|                       | Mineral Spirits     | 64742-47-8 | ACGIH TLV TWA: 200 mg/m <sup>3</sup>     |
|                       | n-Butane            | 106-97-8   | ACGIH TLV TWA 800 ppm                    |
|                       | Acetone             | 67-64-1    | 8-hour Exposure Limit (TLV-TWA): 250 ppm |
|                       | Acetone             | 67-64-1    | 15-minute STEL: 500 ppm                  |
|                       | Methyl ethyl ketone | 78-93-3    | 8-hour Exposure limit (TLV-TWA): 200 ppm |
|                       | Methyl ethyl ketone | 78-93-3    | 15-minute STEL: 300 ppm                  |

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.06.2018

Page 5 of 13

### Self-Etch Primer - Aerosol

| Country (Legal Basis) | Substance           | Identifier | Permissible concentration   |
|-----------------------|---------------------|------------|---|
|                       | Isopropyl Alcohol   | 67-63-0    | ACGIH TLV STEL: 400 ppm   |
|                       | Isopropyl Alcohol   | 67-63-0    | ACGIH TLV TWA: 200 ppm  |
|                       | Titanium Dioxide    | 13463-67-7 | ACGIH TLV TWA: 10 mg/m <sup>3</sup>   |
| United States (OSHA)  | Propane             | 74-98-6    | OSHA PEL TWA 1,000 ppm (1,800 mg/m <sup>3</sup> )   |
|                       | Zinc stearate       | 557-05-1   | PEL: 15 mg/m <sup>3</sup> (Total dust); 5 mg/m <sup>3</sup> (Respirable dust)                 |
|                       | Acetone             | 67-64-1    | TWA: 750 ppm (1800 mg/m <sup>3</sup> )  |
|                       | Acetone             | 67-64-1    | STEL: 1000 ppm (2400 mg/m <sup>3</sup> )  |
|                       | Methyl ethyl ketone | 78-93-3    | TWA: 200 ppm (590 mg/m <sup>3</sup> )   |
|                       | Methyl ethyl ketone | 78-93-3    | STEL: 300 ppm (885 mg/m <sup>3</sup> )  |
|                       | Isopropyl Alcohol   | 67-63-0    | OSHA PEL TWA 400 ppm, 980 mg/m <sup>3</sup>   |
|                       | Titanium Dioxide    | 13463-67-7 | OSHA PEL TWA 15 mg/m <sup>3</sup> (Total dust)  |
| NIOSH                 | n-Butane            | 106-97-8   | NIOSH REL TWA 800 ppm (1,900 mg/m <sup>3</sup> )  |
|                       | Propane             | 74-98-6    | NIOSH REL TWA 1,000 ppm (1,800 mg/m <sup>3</sup> )  |
|                       | Acetone             | 67-64-1    | REL (for up to a 10-hour workday during a 40-hour workweek): 250 ppm (590 mg/m <sup>3</sup> ) |
|                       | Acetone             | 67-64-1    | IDLH: 2500 ppm  |
|                       | Methyl ethyl ketone | 78-93-3    | REL (for up to a 10-hour workday during a 40-hour workweek): 200 ppm (590 mg/m <sup>3</sup> ) |
|                       | Methyl ethyl ketone | 78-93-3    | STEL: 300 ppm (885 mg/m <sup>3</sup> )  |
|                       | Isopropyl Alcohol   | 67-63-0    | NIOSH IDLH 2,000 ppm  |
|                       | Isopropyl Alcohol   | 67-63-0    | NIOSH STEL 500 ppm, 1,225 mg/m <sup>3</sup>   |
|                       | Isopropyl Alcohol   | 67-63-0    | NIOSH TWA 400 ppm, 980 mg/m <sup>3</sup>  |
|                       | Titanium Dioxide    | 13463-67-7 | IDLH: 5,000 mg/m <sup>3</sup>   |
| Australia             | PM Acetate          | 108-65-6   | TWA: 274 mg/m <sup>3</sup> (50 ppm); STEL: 548 mg/m <sup>3</sup> (100 ppm)                    |
|                       | Titanium Dioxide    | 13463-67-7 | TWA: 10 mg/m <sup>3</sup>   |
|                       | Isopropyl Alcohol   | 67-63-0    | TWA: 713 mg/m <sup>3</sup> (150 ppm); STEL: 950 mg/m <sup>3</sup> (200 ppm)                   |
|                       | Acetone             | 67-64-1    | TWA: 1185 mg/m <sup>3</sup> (500 ppm) ; STEL: 2375 mg/m <sup>3</sup> (1000 ppm)               |
|                       | Methyl ethyl ketone | 78-93-3    | TWA: 150 ppm (445 mg/m <sup>3</sup> ) ; STEL: 300 ppm (890 mg/m <sup>3</sup> )                |
| WEEL                  | PM Acetate          | 108-65-6   | WEEL TWA 50.0 ppm   |

#### Biological limit values:

| Substance           | Identifier | Determinant | Sampling time | Permissible limits |
|---------------------|------------|-------------|---------------|--------------------|
| Methyl ethyl ketone | 78-93-3    | MEK         | End of shift. | 2 mg/L             |

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.06.2018

Page 6 of 13

## Self-Etch Primer - Aerosol

| Substance         | Identifier | Determinant | Sampling time                    | Permissible limits |
|-------------------|------------|-------------|----------------------------------|--------------------|
| Isopropyl Alcohol | 67-63-0    | Acetone     | End of shift at end of workweek. | 40 mg/L            |

### Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls.

Biological monitoring may also be appropriate for some substances.

### Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above. Use explosion-proof ventilation equipment.

### Personal protection equipment

#### Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

#### Skin and body protection:

Select glove material impermeable and resistant to the substance.

Wear appropriate clothing to prevent any possibility of skin contact.

#### Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

### General hygienic measures:

Avoid contact with skin, eyes and clothing.

Wash hands before breaks and at the end of work.

Wash contaminated clothing before reuse.

## SECTION 9: Physical and chemical properties

### Information on basic physical and chemical properties

|                                    |                                  |
|------------------------------------|----------------------------------|
| Appearance                         | Aerosol                          |
| Odor                               | Aromatic                         |
| Odor threshold                     | Not determined or not available. |
| pH                                 | Not determined or not available. |
| Melting point/freezing point       | Not determined or not available. |
| Initial boiling point/range        | -44 °C (-47 °F)                  |
| Flash point (closed cup)           | -19 °C (-2 °F)                   |
| Evaporation rate                   | Not determined or not available. |
| Flammability (solid, gas)          | Extremely flammable              |
| Upper flammability/explosive limit | 12.0 Vol %                       |
| Lower flammability/explosive limit | 1.7 Vol %                        |
| Vapor pressure                     | Not determined or not available. |
| Vapor density                      | Not determined or not available. |
| Density                            | Not determined or not available. |

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.06.2018

Page 7 of 13

## Self-Etch Primer - Aerosol

|  |  |
|--|--|
| <b>Relative density</b>                        | Between 0.77 and 0.85 (Water equals 1.00)              |
| <b>Solubilities</b>                            | Not determined or not available.                       |
| <b>Partition coefficient (n-octanol/water)</b> | Not determined or not available.                       |
| <b>Auto/Self-ignition temperature</b>          | Product is not self-igniting                           |
| <b>Decomposition temperature</b>               | Not determined or not available.                       |
| <b>Dynamic viscosity</b>                       | Not determined or not available.                       |
| <b>Kinematic viscosity</b>                     | Not determined or not available.                       |
| <b>Explosive properties</b>                    | In use, may form flammable/explosive vapor-air mixture |
| <b>Oxidizing properties</b>                    | Not determined or not available.                       |

### Other information

|   |       |
|---|-------|
| <b>VOC content (less exempt solvents)</b> | 59.0% |
| <b>MIR Value</b>                          | 0.66  |
| <b>Solids Content</b>                     | 15.5% |

## SECTION 10: Stability and reactivity

### Reactivity:

Does not react under normal conditions of use and storage.

### Chemical stability:

Stable under normal conditions of use and storage.

### Possibility of hazardous reactions:

None under normal conditions of use and storage.

### Conditions to avoid:

None known.

### Incompatible materials:

None known.

### Hazardous decomposition products:

None known.

## SECTION 11: Toxicological information

### Acute toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

#### Substance data:

| Name            | Route  | Result                       |
|-----------------|--------|------------------------------|
| Glycol Ether EP | dermal | LD50 Rabbit male 1,337 mg/kg |

### Skin corrosion/irritation

**Assessment:** Based on available data, the classification criteria are not met.

#### Product data:

No data available.

**Substance data:** No data available.

### Serious eye damage/irritation

**Assessment:** Causes serious eye irritation

#### Product data:

No data available.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.06.2018

Page 8 of 13

## Self-Etch Primer - Aerosol

### Substance data:

| Name                | Result                         |
|---------------------|--------------------------------|
| Acetone             | Causes serious eye irritation. |
| Methyl ethyl ketone | Irritating effect on the eyes. |
| Isopropyl Alcohol   | Causes eye irritation          |
| Glycol Ether EP     | Causes eye irritation.         |

### Respiratory or skin sensitization

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:** No data available.

### Carcinogenicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:**

| Name             | Species          | Result  |
|------------------|------------------|---|
| Titanium Dioxide | Titanium Dioxide | Airborne, unbound particles of respirable size are known to cause cancer. |

### International Agency for Research on Cancer (IARC):

| Name              | Classification   |
|-------------------|--|
| Isopropyl Alcohol | Group 3 - Not classifiable as to its carcinogenicity to humans |
| Titanium Dioxide  | Group 3 - Not classifiable as to its carcinogenicity to humans |
| Mineral Spirits   | Group 3 - Not classifiable as to its carcinogenicity to humans |

**National Toxicology Program (NTP):** None of the ingredients are listed.

### Germ cell mutagenicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:** No data available.

### Reproductive toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:** No data available.

### Specific target organ toxicity (single exposure)

**Assessment:** May cause drowsiness or dizziness

**Product data:**

No data available.

**Substance data:**

| Name                | Result   |
|---------------------|--|
| Acetone             | Specific Target Organ Toxicity, Single Exposure - May cause drowsiness or dizziness. |
| Methyl ethyl ketone | Component affects the central nervous system.  |
| Isopropyl Alcohol   | Component affects the central nervous system.  |



# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.06.2018

Page 9 of 13

## Self-Etch Primer - Aerosol

### Specific target organ toxicity (repeated exposure)

**Assessment:** May cause damage to organs through prolonged or repeated exposure

**Product data:**

No data available.

**Substance data:** No data available.

### Aspiration toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:**

| Name            | Result                                       |
|-----------------|--|
| Mineral Spirits | May be fatal if swallowed and enters airway. |

### Information on likely routes of exposure:

No data available.

### Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

### Other information:

No data available.

## SECTION 12: Ecological information

### Acute (short-term) toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:** No data available.

### Chronic (long-term) toxicity

**Product data:** No data available.

**Substance data:** No data available.

### Persistence and degradability

**Product data:** No data available.

**Substance data:** No data available.

### Bioaccumulative potential

**Product data:** No data available.

**Substance data:** No data available.

### Mobility in soil

**Product data:** No data available.

**Substance data:** No data available.

**Other adverse effects:** No data available.

## SECTION 13: Disposal considerations

### Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

## SECTION 14: Transport information

### United States Transportation of dangerous goods (49 CFR DOT)

|           |      |
|-----------|------|
| UN number | 1950 |
|-----------|------|


# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200


Initial preparation date: 04.06.2018

Page 10 of 13


## Self-Etch Primer - Aerosol

|                                      |   |
|--------------------------------------|---|
| <b>UN proper shipping name</b>       | Aerosols, flammable   |
| <b>UN transport hazard class(es)</b> | 2.1  |
| <b>Packing group</b>                 | None  |
| <b>Environmental hazards</b>         | None  |
| <b>Special precautions for user</b>  | None  |
| <b>Passenger air/rail</b>            | 75 kg   |
| <b>Cargo aircraft only</b>           | 150 kg  |

### International Maritime Dangerous Goods (IMDG)

|                                      |   |
|--------------------------------------|---|
| <b>UN number</b>                     | 1950  |
| <b>UN proper shipping name</b>       | Aerosols  |
| <b>UN transport hazard class(es)</b> | 2.1    |
| <b>Packing group</b>                 | None  |
| <b>Environmental hazards</b>         | None  |
| <b>Special precautions for user</b>  | None  |
| <b>EmS number</b>                    | F-D, S-U  |
| <b>Stowage category</b>              | For AEROSOLS with a maximum capacity of 1 litre: Category A. Segregation as for class 9 but "Separated from" class 1 except division 1.4. For AEROSOLS with a capacity above 1 litre: Category B. Segregation as for the appropriate sub-division of class 2. For WASTE AEROSOLS: Category C. Clear of living quarters. Segregation as for the appropriate sub-division of class 2. |
| <b>Excepted quantities</b>           | E0  |

### International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

|                                      |   |
|--------------------------------------|---|
| <b>UN number</b>                     | 1950  |
| <b>UN proper shipping name</b>       | Aerosols, flammable   |
| <b>UN transport hazard class(es)</b> | 2.1  |
| <b>Packing group</b>                 | None  |
| <b>Environmental hazards</b>         | None  |
| <b>Special precautions for user</b>  | None  |
| <b>ERG code</b>                      | 10L   |
| <b>Excepted quantities</b>           | E0  |
| <b>Passenger and cargo</b>           | 75 kg   |
| <b>Cargo aircraft only</b>           | 150 kg  |
| <b>Limited quantity</b>              | 30 kg G   |

## SECTION 15: Regulatory information

### United States regulations

#### Inventory listing (TSCA):

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.06.2018

Page 11 of 13

### Self-Etch Primer - Aerosol

|            |                     |        |
|------------|---------------------|--------|
| 67-64-1    | Acetone             | Listed |
| 78-93-3    | Methyl ethyl ketone | Listed |
| 74-98-6    | Propane             | Listed |
| 67-63-0    | Isopropyl Alcohol   | Listed |
| 106-97-8   | n-Butane            | Listed |
| 13463-67-7 | Titanium Dioxide    | Listed |
| 557-05-1   | Zinc stearate       | Listed |
| 2807-30-9  | Glycol Ether EP     | Listed |
| 64742-47-8 | Mineral Spirits     | Listed |
| 108-65-6   | PM Acetate          | Listed |

**Significant New Use Rule (TSCA Section 5):** Not determined.

**Export notification under TSCA Section 12(b):** Not determined.

**SARA Section 302 extremely hazardous substances:** Not determined.

**SARA Section 313 toxic chemicals:**

|          |                     |            |
|----------|---------------------|------------|
| 67-64-1  | Acetone             | Not Listed |
| 78-93-3  | Methyl ethyl ketone | Not Listed |
| 67-63-0  | Isopropyl Alcohol   | Not Listed |
| 557-05-1 | Zinc stearate       | Not Listed |

**CERCLA:**

|         |                     |        |       |
|---------|---------------------|--------|-------|
| 67-64-1 | Acetone             | Listed | 5,000 |
| 78-93-3 | Methyl ethyl ketone | Listed | 5,000 |

**RCRA:**

|         |                     |        |      |
|---------|---------------------|--------|------|
| 67-64-1 | Acetone             | Listed | U002 |
| 78-93-3 | Methyl ethyl ketone | Listed | U159 |

**Section 112(r) of the Clean Air Act (CAA):**

|          |          |        |
|----------|----------|--------|
| 74-98-6  | Propane  | Listed |
| 106-97-8 | n-Butane | Listed |

**Massachusetts Right to Know:**

|            |                     |            |
|------------|---------------------|------------|
| 67-64-1    | Acetone             | Listed     |
| 74-98-6    | Propane             | Listed     |
| 13463-67-7 | Titanium Dioxide    | Listed     |
| 67-63-0    | Isopropyl Alcohol   | Listed     |
| 78-93-3    | Methyl ethyl ketone | Listed     |
| 2807-30-9  | Glycol Ether EP     | Not Listed |
| 557-05-1   | Zinc stearate       | Listed     |
| 64742-47-8 | Mineral Spirits     | Not Listed |
| 106-97-8   | n-Butane            | Listed     |
| 108-65-6   | PM Acetate          | Not Listed |

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.06.2018

Page 12 of 13

## Self-Etch Primer - Aerosol

### New Jersey Right to Know:

|            |                     |            |
|------------|---------------------|------------|
| 74-98-6    | Propane             | Listed     |
| 64742-47-8 | Mineral Spirits     | Not Listed |
| 67-63-0    | Isopropyl Alcohol   | Listed     |
| 67-64-1    | Acetone             | Not Listed |
| 78-93-3    | Methyl ethyl ketone | Not Listed |
| 557-05-1   | Zinc stearate       | Not Listed |
| 106-97-8   | n-Butane            | Listed     |
| 108-65-6   | PM Acetate          | Not Listed |
| 13463-67-7 | Titanium Dioxide    | Not Listed |
| 2807-30-9  | Glycol Ether EP     | Not Listed |

### New York Right to Know:

|            |                     |            |
|------------|---------------------|------------|
| 67-64-1    | Acetone             | Listed     |
| 74-98-6    | Propane             | Listed     |
| 13463-67-7 | Titanium Dioxide    | Listed     |
| 67-63-0    | Isopropyl Alcohol   | Listed     |
| 78-93-3    | Methyl ethyl ketone | Listed     |
| 2807-30-9  | Glycol Ether EP     | Not Listed |
| 557-05-1   | Zinc stearate       | Not Listed |
| 64742-47-8 | Mineral Spirits     | Not Listed |
| 106-97-8   | n-Butane            | Listed     |
| 108-65-6   | PM Acetate          | Not Listed |

### Pennsylvania Right to Know:

|            |                     |            |
|------------|---------------------|------------|
| 67-64-1    | Acetone             | Listed     |
| 74-98-6    | Propane             | Listed     |
| 13463-67-7 | Titanium Dioxide    | Listed     |
| 67-63-0    | Isopropyl Alcohol   | Listed     |
| 78-93-3    | Methyl ethyl ketone | Listed     |
| 2807-30-9  | Glycol Ether EP     | Not Listed |
| 557-05-1   | Zinc stearate       | Listed     |
| 64742-47-8 | Mineral Spirits     | Not Listed |
| 106-97-8   | n-Butane            | Listed     |
| 108-65-6   | PM Acetate          | Not Listed |

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.06.2018

Page 13 of 13

### Self-Etch Primer - Aerosol

#### California Proposition 65:

**⚠️WARNING:** This product can expose you to Titanium Dioxide, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

### SECTION 16: Other information

**Abbreviations and Acronyms:** None

#### Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

**NFPA:** 2-4-3

**HMIS:** 2-4-3

**Initial preparation date:** 04.06.2018

**End of Safety Data Sheet**